

## FEATURES AND BENEFITS




- 316 marine grade stainless steel faceplate
- Low profile, high strength, sealed back box for greater performance and durability
- LED downlight
- Surface mounted
- Downward facing microphone
- **THS** Horwood quality sound
- IP64 rated keypad
- Time clock with 3 profiles
- Backlit, vandal resistant keypad
- Timed 'trade' button
- 100 PIN codes for coded entry
- 100 authorised dial to open numbers

Dimensions: H 216 x W 99 x D 40 mm    Number of Users : 1

## DOWNLOAD THE 'Commtel CONTROL' APP

- Easy remote programming to fully control and configure.



- Please pay particular attention to the Safety Message Contents included on the App front page (*View Safety Message*).



**OPEN | LATCH | CLOSE**  
at the click of a button



### EASY TO USE

- Each single call point has the ability to cascade through 3 landline or mobile numbers. Once answered, if the recipient wants to grant access to the visitor they simply press the # key on their phone.



### DOWNLOADABLE ACTIVITY LOGS

- Download the last 10,000 interactions with the unit and see who is gaining entry, how and when.
- A great security feature for free!



### ACCESS CONTROL

- With built in keypad and dial to open, you can authorise entry to specific individuals with either a PIN code or by registering their mobile number. You can even time restrict entry for certain individuals if required!



### EASY TO INSTALL

- Minimal cabling:
  - Simply plug (12 V) PSU into 240V AC power.
  - Connect relays into entry equipment.
  - Connect antenna and register onto to local mobile network (*TG Telecom SIM provided\**).
- No access is required to individual properties for installations or maintenance.



### CONFIGURATION

- Standalone as standard.
- Not compatible with the Telpad or external DIN relay extension.



### TWO YEAR WARRANTY

- Parts only.
- Programming support not included.

\* Subject to activation order.

## TECHNICAL SPECIFICATION

- **Power** 12V 1A DC PSU fitted with a 3A fuse (*supplied and must be dedicated to the Optimus intercom unit*).
- **Power Consumption** 120mA Idle @ 12V.
- **Telephone Type** Standard DTMF (*Dual Tone Multi Frequency*) generating telephone, cordless or mobile phone.
- **Programming** Remotely programmable via App and SMS.
- **Relays** 3: 1x 2A, 2x 200mA
- **Relay Activation Time** 1 – 240 seconds, adjustable remotely.
- **Inputs** 2x Volt free auxiliary inputs. The auxiliary input is for volt free exit release type buttons only. Damage will result if feeding voltage or any other item that is not a volt free contact.
- **Time Clocks** The on-board time clock enables custom profile functions to be activated.
- **Authorised Call Access** 100 telephone numbers can be stored. Calling the unit, from an authorised telephone number, activates a predetermined relay.
- **Volume** Adjustable 1 - 9 levels.
- **Network Capability** 4G LTE.
- **Antenna** 1x 4G PUK antenna with 2m lead and 90° MMCX connection. (*1m lead available upon request. Longer leads available at additional cost and longer lead time*).

EU CE Declaration of Conformity and Radio Equipment Directive is available at [www.commtel-uk.com](http://www.commtel-uk.com) | GB-RH10 9RB



Raising Standards  
Safety Assured

